

Document #: APM-RG-ROHS-1050-D

Date: August 18, 2021

44 Honeck Street Englewood, NJ 07631 USA Phone: (201) 569-5700 Fax: (201) 569-4106 info@apmhexseal.com www.apmhexseal.com

Declaration of Conformity to RoHS3, Directive (EU) 2015/863 for Lever-Actuated Circuit Breaker Boots

APM HEXSEAL is committed to conducting its business in an environmentally, socially, and ethically responsible manner, complying with all applicable laws and regulations of those countries where we do business. Part of this commitment includes the safe use and identification of materials and/or substances in excess of the allowable thresholds per the applicable requirements of the EU Directive 2015/863, also known as RoHS3 (Restriction of Hazardous Substances) in electrical and electronic equipment.

Material/Substance	Threshold Level
Cadmium	0.01%
Hexavalent Chromium	0.1%
Lead •	0.1%
Mercury	0.1%
Polybrominated Biphenyls (PBBs)	0.1%
Polybrominated Diphenyl Ethers (PBDE)	0.1%
Bis(2-Ethylhexyl) Phthalate (DEHP)	0.1%
Benzyl Butyl Phthalate (BBP)	0.1%
Dibutyl Phthalate (DBP)	0.1%
Diisobutyl Phthalate (DIBP)	0.1%

All threshold levels represent maximum concentration by weight in homogeneous materials.

This document certifies that, to the best of our knowledge, based on the published specifications and information provided by our suppliers, the APM Hexseal products shown in the list below do not contain the following materials and/or substances in excess of the allowable threshold levels, with the exception of Lead, which falls under **Exemption 6(c)** outlined in **Annex III** to the above Directive.

Series	
Type HE####*	
Type CT####*	
Type 1113/XX* & C1113/XX*	
Type 1077*	

The presence of "XX" in a series number denotes additional digits (1 to 99).

The presence of "####" in a series number denotes 4 additional digits (1000 to 1100).

* NOTE: Series numbers may be followed by various suffix codes.

Signed for on behalf of

APM Hexseal Corporation

Julian Belizaire, Director of Quality



[•] NOTE: Lead as an alloying element is allowed as a percentage of weight: Steel 0.35%, Aluminum 0.40%, and Copper Alloy 4.0%.